

OpioidRisk Homepage

```
ul li {margin-bottom: 8px;} /*
http://stopdesign.com/eg/buttons/3.0/code.html# */ .btn { display:inline-block;
background:none; margin:5px; padding:5px; border-width:0; overflow:visible;
font:100%/1.2 Arial,Sans-serif; font-weight: bold; text-decoration:none;
color:#333; } * html button.btn { padding-bottom:1px; } /* Immediately below
is a temporary hack to serve the following margin values only to Gecko browsers
Gecko browsers add an extra 3px of left/right padding to button elements which can't be
overridden. Thus, we use -3px of left/right margin to overcome this. */
html:not([lang*=""]) button.btn { margin:0 -3px; } .btn span { background:#ddd
repeat-x 0 0; margin:0; padding:5px; border-left:1px solid #bbb;
border-right:1px solid #aaa; } * html .btn span { padding-top:0; } .btn span
span { position:relative; padding:3px .4em; border-width:0; border-top:1px
solid #bbb; border-bottom:1px solid #aaa; } /* pill classes only needed if using
pill style buttons ( LEFT | CENTER | RIGHT ) */ button.pill-l span { border-right-width:0;
} button.pill-l span span { border-right:1px solid #bbb; } button.pill-c span {
border-right-style:none; border-left-color:#fff; } button.pill-c span span {
border-right:1px solid #bbb; } button.pill-r span { border-left-color:#fff; } /*
only needed if implementing separate hover/focus/active state for buttons */ .btn:hover
span, .btn:hover span span, .btn:focus span, .btn:focus span span { cursor:pointer; /*
important for any clickable/pressable element */ border-color:#9cf !important;
background:#fff; color:#a5333b } .btn:active span { background-position:0
-400px; outline:none; } .btn:focus, .btn:active { outline:none; /* doesn't seem to
be respected for , only */ } /* use if one button should be the 'primary' button */
.primary { font-weight:bold; color:#000; }
```

[Build Skills to Minimize the Risk of Prescription Opioid Misuse](#)